UNITED STATAS DEPARTMENT OF COMMERCE United States Palent and Trademark Office Address: COMMISSIONER FOR PATENTS P. 10 BO 1450 Alexandra, Virginia 22313-1450

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/623,234	07/18/2003	Jeffrey S. Kinne	EMC2-144PUS	2729
	7590 05/31/200 SHARKANSKY	7	EXAMINER	
PO BOX 557			RABOVIANSKI, ANTON I	
MASHPEE, M	A 02649	•	ART UNIT	PAPER NUMBER
			2188	
		·		
			MAIL DATE	DELIVERY MODE
			05/31/2007	PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

	Analization No.	A!	
	Application No.	Applicant(s)	
Office Action Summary	10/623,234	KINNE, JEFFREY S.	<u>-</u>
omec Action Cummary	Examiner	Art Unit	
The MAU INO DATE of this communication	Anton Rabovianski	2188	
The MAILING DATE of this communication appeariod for Reply	pears on the cover sheet wit	n the correspondence address	
A SHORTENED STATUTORY PERIOD FOR REPL WHICHEVER IS LONGER, FROM THE MAILING D - Extensions of time may be available under the provisions of 37 CFR 1. after SIX (6) MONTHS from the mailing date of this communication. - If NO period for reply is specified above, the maximum statutory period - Failure to reply within the set or extended period for reply will, by statut Any reply received by the Office later than three months after the mailin earned patent term adjustment. See 37 CFR 1.704(b).	DATE OF THIS COMMUNIC 136(a). In no event, however, may a re will apply and will expire SIX (6) MONT e, cause the application to become ABA	ATION. ply be timely filed HS from the mailing date of this communication. ANDONED (35 U.S.C. § 133).	
Status			
 Responsive to communication(s) filed on 17 E This action is FINAL. 2b) This Since this application is in condition for allowated closed in accordance with the practice under the second se	s action is non-final. ince except for formal matte	• •	
•	en parto Quayro, 1000 O.B.	11, 400 0.0. 210.	
Disposition of Claims			
4) Claim(s) 1 and 2 is/are pending in the applicate 4a) Of the above claim(s) is/are withdrate 5) Claim(s) is/are allowed. 6) Claim(s) 1 and 2 is/are rejected. 7) Claim(s) is/are objected to. 8) Claim(s) are subject to restriction and/or	wn from consideration.		
Application Papers		·	
9)☐ The specification is objected to by the Examine 10)☒ The drawing(s) filed on 18 July 2003 is/are: a) Applicant may not request that any objection to the Replacement drawing sheet(s) including the correct 11)☐ The oath or declaration is objected to by the Examine	accepted or b) ☐ object drawing(s) be held in abeyand ction is required if the drawing(s	e. See 37 CFR 1.85(a). s) is objected to. See 37 CFR 1.121(d).	
Priority under 35 U.S.C. § 119			
12) Acknowledgment is made of a claim for foreign a) All b) Some * c) None of: 1. Certified copies of the priority document 2. Certified copies of the priority document 3. Copies of the certified copies of the priority document application from the International Bureat * See the attached detailed Office action for a list	ts have been received. ts have been received in Ap prity documents have been r u (PCT Rule 17.2(a)).	plication No eceived in this National Stage	
Attachment(s)			
 Notice of References Cited (PTO-892) Notice of Draftsperson's Patent Drawing Review (PTO-948) Information Disclosure Statement(s) (PTO/SB/08) Paper No(s)/Mail Date 	Paper No(s)	nmary (PTO-413) /Mail Date ormal Patent Application -	•

Application/Control Number: 10/623,234

Art Unit: 2188

DETAILED ACTION

This Office Action is responsive to the Application filed on 07/18/2003.

Claims 1-2 are presented for examination. Claims 1-2 are pending.

Claim Rejections - 35 USC § 102

The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless -

(b) the invention was patented or described in a printed publication in this or a foreign country or in public use or on sale in this country, more than one year prior to the date of application for patent in the United States.

Claims 1 and 2 are rejected under 35 U.S.C. 102(b) as being anticipated by Gaytan et al. (US 5,638,367).

With respect to claim 1, the Gaytan et al. reference teaches a system for storing a block of data, such block of data comprising different packets of data stored in correspondingly different sections of a memory (fig. 1), and for gathering selected portions of the stored packets and then transferring the selected portions of the gathered packets into a transmitted block of data having the selected portions appended contiguously one to the other (col. 1, lines 28-39), such memory storing the packets in word-based locations, the word-based locations having a common word width, W, the stored packets have a variable number of bytes, the bytes of the gathered selected portions of the stored packets being offset from initial byte positions of the stored packets (col. 6, lines 34-67 and col. 9, lines 31-67), the packets having variable offsets (fig. 1, 6a and 7a), such system comprising:

Art Unit: 2188

a sampling register (fig. 1, fig. 3 and fig. 6a, i.e. there must be a register between host memory 395 and word packing circuit 600 in fig. 3) having W byte locations for storing W bytes read from a selected one of the word-based locations of the memory, such read bytes being bytes of a currently gathered one of the packets (col. 6, lines 34-44);

a shifter (fig. 6a, el. 610 and 615) for shifting the bytes stored in the sampling register, such bytes being shifted as a function of the offset of the currently gathered one of the packets and the number of bytes in a prior gathered one of the packets (col. 6, lines 53-65);

an accumulator register (fig. 6b, el. 660) having W byte locations for storing the shifted bytes in response to a clock pulse (col. 9, lines 43-44);

a staging register (fig. 6b, el. 665) having W byte locations, for storing the bytes stored in the accumulator register in response to a subsequent clock pulse (col. 9, lines 44-47); and

a multiplexer (fig. 6b, el. 675) having a W sections, each of the W sections being coupled to a corresponding one of the W byte locations of the accumulator register and a corresponding one of the W byte locations of the staging register, each one of the sections coupling to an output thereof the byte location of the accumulator register or the byte location of the staging register selectively in accordance with the number of bytes in the prior gathered ones of the packets and the number of bytes being gathered from the currently gathered one of the packets (col. 9, lines 31-67 and col. 10, lines 25-30) to provide at an output of the multiplexer bytes to be transmitted as the transmitted

Application/Control Number: 10/623,234

Art Unit: 2188

block of data having the selected portions appended contiguously one to the other (fig 1 and fig. 7a-7i).

Regarding claim 2, Gaytan et al. teach a system for distributing different packets of data stored in continuous locations of a memory (fig. 1), such memory storing the packets in word-based locations, the word-based locations having a common word width, W, the stored packets have a variable number of bytes, the bytes of the distributed packets to be offset from initial byte positions (col. 6, lines 34-67 and col. 9, lines 31-67), the offsets being variable (fig. 1, 6a and 7a), such system comprising:

a sampling register (fig. 1 and fig. 6a, i.e. there must be a register between host memory 395 and word packing circuit 600 in fig. 3) having W byte locations for storing W bytes read from a selected one of the word-based locations of the memory, such read bytes being bytes of a currently distributed one of the packets (col. 6, lines 34-44);

a shifter (fig. 6a, el. 610 and 615) for shifting the bytes stored in the sampling register, such bytes being shifted as a function of the offset of the currently distributed one of the packets and the number of bytes in a prior distributed one of the packets (col. 6, lines 53-65);

an accumulator register (fig. 6b, el. 660) having W byte locations for storing the shifted bytes in response to a clock pulse (col. 9, lines 43-44);

a staging register (fig. 6b, el. 665) having W byte locations, for Storing the bytes stored in the accumulator register in response to a subsequent clock pulse (col. 9, lines 44-47); and

Art Unit: 2188

a multiplexer (fig. 6b, el. 675) having a W sections, each of the W sections being coupled to a corresponding one of the W byte locations of the accumulator register and a corresponding one of the W byte locations of the staging register, each one of the sections coupling to an output thereof the byte location of the accumulator register or the byte location of the staging register selectively in accordance with the number of bytes in the prior distributed ones of the packets and the number of bytes being distributed from the currently distributed one of the packets-to provide at an output of the multiplexer (fig. 1; fig. 7a-7i; col. 9, lines 31-67 and col. 10, lines 25-30).

Conclusion

The prior art made of record and not relied upon is considered pertinent to applicant's disclosure. Kaganoi et al. (US 6,026,450) disclose a data transfer control system which uses fields of a table to control the data transfer. Turner et al. (US 6,865,656) disclose a system for efficient transfer of data between custom application specific integrated circuit hardware and an embedded microprocessor. Yee et al. (US 6,466,581) disclose a multistream data packet transfer apparatus that pack data received from different fragments of memory as a single packet for use by a DSP. Padmanabhan et al. (US 6,567,902) disclose a system for packing data into a destination register.

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Anton Rabovianski whose telephone number is 571-270-1026. The examiner can normally be reached on M-Th 9:00am-7:30pm EST.

Application/Control Number: 10/623,234

Art Unit: 2188

Page 6

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Hyung S. Sough can be reached on 571-272-6799. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

Anton Rabovianski

May 21, 2007

5-29-07